



DORMA BTS-80-2 FLOOR CLOSER, SPECIAL CEMENT CASE, SPINDLE, FRONT ANCHOR BRACKET, COVER PLATE FURNISHED BY BLUMCRAFT. (TYPICAL)

BOX MUST BE SECURELY GROUDED INTO CONCRETE FLOOR STRUCTURE AT INSTALLATION USING NON-SHRINK OR EXPANDING TYPE GROUT (NOT BY BLUMCRAFT)

BLUMCRAFT SUGGESTS THE FOLLOWING FLOOR PREPARATION DIMENSIONS:

3" (+1/8", -0") DEEP,  
 4 1/2" (+1/4", -0") WIDE,  
 14" (+1/8", -0") LONG.

4 1/8" WIDE x 13 9/16" LONG

TOLERANCES: +.005 - .005 DECIMALS + 1/64 - 1/64 FRACTIONS

UNLESS OTHERWISE SPECIFIED

*Blumcraft*

OF PITTSBURGH

H-110 PANIC HARDWARE WITH THRESHOLD RAMP STRIKE

REVISIONS	DATE	DN	CH

DRAWN BY KC 7/13/05

CHECKED BY -

SCALE FULL

DWG. NO. CAD-1301FC-4

SHEET 1 OF 1